

Bush Hog® RD Series Rotary Cutters

BUSH HOG® FEATURES
Front Belting & Rear Band
Solid Rubber Tail Wheel
Fabricated Reinforced Deck
Welded-On Front Skids
Floating Hitch



Model RD5

MODELS	RD5	RD6
Cutting Width	5 ft.	6 ft.
Cutting Capacity	Up to 1-inch Diameter	
Cutting Height (Minimum)	1 1/2 inches	
Dimensions (width x length)	5 ft. 6 in. wide x 7 ft. 4 in. long	6 ft. 6 in. wide x 8 ft. 11 in. long
Type Hitch	3-Point Lift, Category 1 Standard	
Deck Thickness	11 gauge	
Size Bands	11 gauge	
Driveshaft	ASAE Category 3	
Gearbox	60 HP*	
Tractor PTO Speed	540 RPM	
Driveline Protection	Shear Pin	
Blade Holder	Bar Type	
Blades	1/2" x 3"	
Blade Tip Speed	12,468 FPM	12,963 FPM
Tires	Solid Rubber	
Tractor HP (Minimum)	20 PTO	25 PTO
Front and Rear Deflectors	Front Belting and Rear Band	
Approx. Weight	522 lbs	638 lbs
Warranty	1 year limited warranty	

* Field Performance Rating.