

# BUSH HOG®



*Performance  
You Can  
Count  
On™*

## CROP FLAIL SHREDDERS

BRC SERIES | BRC115, BRC118, BRC120, BRC125





BRC Series

## **CROP FLAIL SHREDDER**



The Bush Hog® line of BRC row crop flails provides superior shredding performance in a number of crop conditions, cotton, BT corn stalks, milo, rice, wheat, and vegetable stubble are no match for these machines. Designed to handle higher volumes of crop residue, the BRC models from Bush Hog® are equipped with a re-cutter bar design which allows the material to be cut three times, thereby speeding up crop decomposition. Computer-balanced 10 3/4-inches diameter rotors ensure smooth operation in tough conditions. Triple-lipped, sealed double row spherical roller bearings, combined with reversible, hard surfaced cutter knives and 3/16-inch internal steel liners at critical wear areas, ensure greater reliability in tough conditions. Bush Hog® units are available in 15, 18, 20, and 25-foot operating widths to match various crop conditions and row spacings. Depending on the model, the BRC row crop flails are available with pull, lift, or semi-mount hitches. These BRC row crop flails are ready to shred!

## Bush Hog® Features

- **Blades chops through cotton**, BT corn stalks, milo, rice, wheat, or vegetable stubble.
- **Re-Cutter Bar speeds up decomposition** of plant residue to get nutrients back into the ground quickly.
- **Frame provides ground cover** to minimize wind and water erosion.
- **Sizes available in 15, 18, 20, and 25-foot widths** to fit your crop's row spacing.

### SPECIFICATIONS

	<b>BRC115</b>	<b>BRC118</b>	<b>BRC120</b>	<b>BRC125</b>
<b>Cutting Width</b>	180-inches	216-inches	240-inches	300-inches
<b>Overall Width</b>	204-inches	240-inches	264-inches	324-inches
<b>Cutting Height</b>	1-inch to 18-inches	1-inch to 18-inches	1-inch to 18-inches	1-inch to 18-inches
<b>Hitch Types</b>	CAT II-III QH Lift, Semi-Mount, or Pull Type	CAT II-III QH Lift, Semi-Mount, or Pull Type	CAT II-III QH Lift, Semi-Mount, or Pull Type	Lift, Semi-Mount, or Pull Type
<b>Cutter Shaft Diameter</b>	10 3/4-inches	10 3/4-inches	10 3/4-inches	10 3/4-inches
<b>Min PTO HP Required</b>				
<b>Lift</b>	120 HP	130 HP	130 HP	N/A
<b>Semi-Mount</b>	100 HP	110 HP	120 HP	150 HP
<b>Pull-Type</b>	100 HP	110 HP	120 HP	140 HP
<b>Gearbox Rating**</b>	207 HP	207 HP	207 HP	207 HP
<b>PTO Type</b>	1,000 RPM	1,000 RPM	1,000 RPM	1,000 RPM
<b>Blades</b>	Hard Surfaced: No "D" Rings			
<b>Blade Tip Speed (FPM)</b>	12,620	12,620	12,620	12,000
<b>No. of Blades</b>	168	200	216	272
<b>Driveline Size</b>	Cat. 5 or 6	Cat. 5 or 6	Cat. 5 or 6	Cat. 5 or 6
<b>Driveline Protection</b>	5 x 5V Banded Belt	5 x 5V Banded Belt	5 x 5V Banded Belt	5 x 5V Banded Belt
<b>Rotor Bearing Protection</b>	Anti-Wrap Seal Protector			
<b>Cutter Shaft Bearings</b>	2 9/16-inches Double Row Spherical Roller, Triple Sealed			
<b>Hood Thickness</b>	3/16-inch with 3/16-inch Internal Wear Liner			
<b>End Plate Thickness</b>	1/4-inch	1/4-inch	1/4-inch	1/4-inch
<b>No. of Axles</b>	4	4	4	4
<b>Wheel Hub Size</b>	5-Bolt	5-Bolt	6-Bolt	6-Bolt
<b>Tire Size/Type</b>	6.70-5 Ribbed	6.70-5 Ribbed	9.5L-15 Ribbed	9.5L-15 Ribbed
<b>Safety Lights</b>	Standard	Standard	Standard	Standard
<b>Weight (Approx.)</b>	4,600-lbs.	4,960-lbs.	5,150-lbs.	6,300-lbs.



2501 Griffin Ave.  
Selma, Alabama 36703  
Tel: 800-363-6096  
Fax: 334-874-2701  
[www.bushhog.com](http://www.bushhog.com)

Bush Hog and  (hog icon) are registered trademarks of Alamo Group Inc. Copyright © 2018